

(Sand Blasted, Polished, Electro Polished)

Features:

- * Heavy duty units for large scale commercial / industrial applications
- * Construction material : SS316L , SS304
- * Easy installation and maintenance
- * Ideal for high-temperature applications (Max. 390 °F - 150 °C)
- * Maximum pressure : 125 psi (8.6 bar)
- * Number of cartridges : 3, 5, 7, 13, 21, 27, ... elements
- * Size of cartridges : 10" , 20" , 30" , 40"
- * Accepts complete range of standard double open end (DOE) cartridges
- * Sealing gasket : Buna-N

Multy Filter Cartridge Housing applications :

- Pre filtration for Reverse Osmosis units
- Drinking water filtration
- Surface water filtration
- Boilers , cooling towers & chill water filtration
- Processed & bottled water



FH40-7

FH40-21

Multy Filter Cartridge Housings Specification & Performance

Model	Recommended Flow Rates	Dimensions Height x Dia	Filter Cartridges			Pipe Size (NPT)
			No.	Dia.	Length	
FH10-3	11 Gpm (41 L/min)	24" x 7" (600 x 180)	3	2½" (76 mm)	10" (254 mm)	1"
FH10-5	17 Gpm (64 L/min)	24" x 9" (600 x 230)	5	2½" (76 mm)	10" (254 mm)	1½"
FH10-7	25 Gpm (94 L/min)	24" x 11" (600 x 280)	7	2½" (76 mm)	10" (254 mm)	1½"
FH20-3	24 Gpm (90 L/min)	29" x 7" (737 x 180)	3	2½" (76 mm)	20" (508 mm)	1"
FH20-5	40 Gpm (150 L/min)	29" x 9" (737 x 230)	5	2½" (76 mm)	20" (508 mm)	1½"
FH20-7	56 Gpm (212 L/min)	29" x 11" (737 x 280)	7	2½" (76 mm)	20" (508 mm)	2"
FH30-7	84 Gpm (318 L/min)	39-3/4" x 11" (1010 x 280)	7	2½" (76 mm)	30" (767 mm)	2½"
FH40-7	125 Gpm (473 L/min)	49-3/4" x 11" (1264 x 280)	7	2½" (76 mm)	40" (1016 mm)	2½"
FH40-21	380 Gpm (1410 L/min)	70" x 20" (1778 x 508)	21	2½" (76 mm)	40" (1016 mm)	3"



FH20-7